

View Online at <https://aerobasegroup.com/nsn/5999-00-139-5976>

**Thread Class:**

2b

**Body Style:**

Rectangular

**Slot Depth:**

Any acceptable

**Slot Width:**

Any acceptable

**Shaft Diameter:**

0.187 inches

**Shaft Length:**

0.060 inches

**Frequency Rating:**

5.000 kilohertz

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

1.250 inches

**Body Width:**

1.030 inches

**Shaft Style:**

Round, slotted

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches

**Longest Vertical Distance Between Mounting Centers:**

0.800 inches

**Operating Temperature Range:**

-54.0 to 110.0 degrees celsius

**Mounting Facility Quantity:**

2

**Voltage Rating:**

12.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

93.000 ohms

**Output Impedance Rating:**

2.000 kilohms

**Frequency Bandwidth:**

7000.0 kilohertz

**Body Depth:**

0.310 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

2 position diagonal

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

110.000 nanoseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

10.0 nanoseconds

**Terminal Type And Quantity:**

4 pin

**Thread Size And Series/type Designator:**

0.086-56 unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100