

View Online at <https://aerobasegroup.com/nsn/5999-00-140-9243>

Thread Class:

2a and 6a

Thread Pitch Diameters:

+0.1177/+0.1214 inches

Body Style:

Rectangular

Body Length:

2.000 inches

Body Width:

1.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.625 inches

Longest Vertical Distance Between Mounting Centers:

0.625 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

2

Voltage Rating:

500.000 volts

Material And Location:

Steel

Surface Treatment And Location:

Lacquer, gray and steel, tin-dipped overall

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

1.000 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position diagonal

Attenuation In Decibels:

6.000

Signal Delay Method:

Electromechanical

Delay Time Variation Method:

Variable

Section Delay Time:

250.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

0.500 nanoseconds

Terminal Type And Quantity:

3 wire loop

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100