

View Online at <https://aerobasegroup.com/nsn/5999-00-162-1889>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1257 to 0.1437 inches

**Body Style:**

Rectangular

**Slot Depth:**

0.130 inches

**Slot Width:**

0.050 inches

**Shaft Diameter:**

Any acceptable

**Shaft Length:**

0.490 inches

**Frequency Rating:**

Not rated

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

6.530 inches

**Body Width:**

1.250 inches

**Shaft Style:**

Round, slotted

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

5.000 inches

**Operating Temperature Range:**

Not rated

**Stud Length:**

0.470 inches

**Mounting Facility Quantity:**

2

**Voltage Rating:**

Not rated

**Material And Location:**

Steel, qq-s-763, class 303, cond a body

**Surface Treatment And Location:**

Lacquer, gray body

**Input Impedance Rating:**

Not rated

**Output Impedance Rating:**

Not rated

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.660 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

300.000 nanoseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

4 wire loop

**Thread Size And Series/type Designator:**

0.164-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100