

View Online at <https://aerobasegroup.com/nsn/5999-00-162-1889>

Thread Class:

2a

Thread Pitch Diameters:

+0.1257 to 0.1437 inches

Body Style:

Rectangular

Slot Depth:

0.130 inches

Slot Width:

0.050 inches

Shaft Diameter:

Any acceptable

Shaft Length:

0.490 inches

Frequency Rating:

Not rated

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

6.530 inches

Body Width:

1.250 inches

Shaft Style:

Round, slotted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.000 inches

Operating Temperature Range:

Not rated

Stud Length:

0.470 inches

Mounting Facility Quantity:

2

Voltage Rating:

Not rated

Material And Location:

Steel, qq-s-763, class 303, cond a body

Surface Treatment And Location:

Lacquer, gray body

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.660 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

300.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

4 wire loop

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100