

View Online at <https://aerobasegroup.com/nsn/5999-00-167-1122>

Body Style:

Capsule, divided

Frequency Rating:

Not rated

Body Length:

2.000 inches

Body Width:

0.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

1.600 inches

Operating Temperature Range:

-0.0 to 75.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

200.000 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sdg

Surface Treatment And Location:

Enamel, tt-e-516

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.750 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.500

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

120.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

5.0 nanoseconds

Terminal Type And Quantity:

4 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100