NSN 5999-00-167-1122



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-167-1122 **Body Style:** Capsule, divided Frequency Rating: Not rated **Body Length:** 2.000 inches **Body Width:** 0.500 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.500 inches **Longest Vertical Distance Between Mounting Centers:** 1.600 inches **Operating Tempurature Range:** -0.0 to 75.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** 200.000 volts **Material And Location:** Plastic, diallyl phthalate, mil-m-14, type sdg **Surface Treatment And Location:** Enamel, tt-e-516 Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.750 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:**

0.500

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

NSN 5999-00-167-1122

Delay Line - Page 2 of 2



120.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

5.0 nanoseconds

Terminal Type And Quantity:

4 wire leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100