

View Online at <https://aerobasegroup.com/nsn/5999-00-167-1122>

**Body Style:**

Capsule, divided

**Frequency Rating:**

Not rated

**Body Length:**

2.000 inches

**Body Width:**

0.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.600 inches

**Operating Temperature Range:**

-0.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

200.000 volts

**Material And Location:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Surface Treatment And Location:**

Enamel, tt-e-516

**Input Impedance Rating:**

Not rated

**Output Impedance Rating:**

Not rated

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.750 inches

**Mounting Facility:**

Terminal

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

0.500

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

120.000 nanoseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

5.0 nanoseconds

**Terminal Type And Quantity:**

4 wire leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100