## NSN 5999-00-182-7215

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-182-7215

#### **Thread Class:**

2b

Body Style:

Rectangular

#### **Body Length:**

4.000 inches

#### **Body Width:**

1.500 inches

#### Individual Section Quantity:

1

#### Longest Horizontal Distance Between Mounting Centers:

3.625 inches

#### Longest Vertical Distance Between Mounting Centers:

1.125 inches

#### **Operating Tempurature Range:**

#### -40.0/+100.0 degrees celsius

#### **Mounting Facility Quantity:**

4

#### Voltage Rating:

5.000 volts

#### Input Impedance Rating:

500.000 ohms

#### **Output Impedance Rating:**

500.000 ohms

#### **Body Depth:**

0.625 inches

#### Mounting Facility:

Threaded bushing

#### Mounting Provision Arrangement Style:

Four position rectangular

#### Attenuation In Decibels:

1.000

#### **Delay Time Variation Method:**

Tapped

#### Section Delay Time:

1.050 microseconds single section

### Segment Quantity Per Section:

17 single section

#### Segment Delay Time:

20.000 nanoseconds single section 5th segment

#### Pulse Rise Time Rating:

100.0 nanoseconds

# NSN 5999-00-182-7215

Delay Line - Page 2 of 2



## Terminal Type And Quantity:

18 pin

## Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A32100