

View Online at <https://aerobasegroup.com/nsn/5999-00-189-1696>

**Body Style:**

Rectangular

**Body Length:**

0.700 inches

**Body Width:**

0.390 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.600 inches

**Longest Vertical Distance Between Mounting Centers:**

0.300 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:**

14

**Voltage Rating:**

25.000 volts

**Material And Location:**

Aluminum alloy, qq-a-225/5, alloy 2017, t4

**Surface Treatment And Location:**

Anodized, mil-a-8625, type 3, class 1

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Body Depth:**

0.210 inches

**Mounting Facility:**

Terminal

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

60.000 nanoseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

6.000 nanoseconds single section all segments

**Pulse Rise Time Rating:**

20.0 nanoseconds

**Terminal Type And Quantity:**

14 wire leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100