

View Online at <https://aerobasegroup.com/nsn/5999-00-189-1696>

Body Style:

Rectangular

Body Length:

0.700 inches

Body Width:

0.390 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.600 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

14

Voltage Rating:

25.000 volts

Material And Location:

Aluminum alloy, qq-a-225/5, alloy 2017, t4

Surface Treatment And Location:

Anodized, mil-a-8625, type 3, class 1

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

0.210 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

60.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

6.000 nanoseconds single section all segments

Pulse Rise Time Rating:

20.0 nanoseconds

Terminal Type And Quantity:

14 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100