## NSN 5999-00-205-8951

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-205-8951 **Body Style:** Rectangular **Shaft Length:** 0.120 inches **Body Length:** 2.250 inches **Body Width:** 0.750 inches **Shaft Style:** Round, slotted **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.800 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Plastic, diallyl phthalate, mil-m-14, type mdg Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Body Depth:** 0.350 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 0.500 **Signal Delay Method:** Inductance **Delay Time Variation Method:** Variable **Section Delay Time:** 

125.000 nanoseconds single section **Pulse Rise Time Rating:** 

4.1 nanoseconds

## NSN 5999-00-205-8951

Delay Line - Page 2 of 2



Terminal	Type	Δnd	Quantity:	
ı <del>C</del> ı IIIIII aı	ı ype	Allu	Qualitity.	

4 wire leads

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32100