NSN 5999-00-215-4837

Electrical Contact - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-00-215-4837

Red Overall Length: 0.766 inches Overall Diameter: Between 0.063 inches and 0.068 inches Cable Entrance Diameter: Between 0.044 inches and 0.048 inches Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact Style Designator:
Overall Diameter: Between 0.063 inches and 0.068 inches Cable Entrance Diameter: Between 0.044 inches and 0.048 inches Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Overall Diameter: Between 0.063 inches and 0.068 inches Cable Entrance Diameter: Between 0.044 inches and 0.048 inches Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Between 0.063 inches and 0.068 inches Cable Entrance Diameter: Between 0.044 inches and 0.048 inches Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Cable Entrance Diameter: Between 0.044 inches and 0.048 inches Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Between 0.044 inches and 0.048 inches Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Current Rating In Amps: 7.5 Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Mounting Method: Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Spring tension Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Material: Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Copper alloy body Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Surface Treatment: Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Gold contact Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Surface Treatment Specification: Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Mil-g-45204, type 2, cl 1 military specification single treatment response contact
Style Designator:
, ,
Pin contact
Terminal Type And Quantity:
1 crimp axially at one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A222a0
Mil-std (military Standard):
Mil-g-45204 spec.