

View Online at <https://aerobasegroup.com/nsn/5999-00-225-8375>

Body Style:

Rectangular

Hole Diameter:

0.100 inches

Frequency Rating:

5.000 megahertz

Body Length:

3.230 inches

Body Width:

0.855 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.499 inches

Longest Vertical Distance Between Mounting Centers:

0.375 inches

Operating Temperature Range:

-55.0/+175.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

9.000 volts

Material And Location:

Any acceptable

Input Impedance Rating:

93.000 ohms

Output Impedance Rating:

93.000 ohms

Body Depth:

0.348 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Electromechanical

Delay Time Variation Method:

Tapped

Section Delay Time:

200.000 nanoseconds single section

Segment Quantity Per Section:

20 single section

Segment Delay Time:

10.000 nanoseconds single section all segments

Pulse Rise Time Rating:

35.0 nanoseconds

Terminal Type And Quantity:

23 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100