
Electronic Shielding Gasket - Page 1 of 2





Cross Sectional Shape: Mesh and composition Hole Diameter: 0.187 inches **Overall Length:** 14.500 inches **Tempurature Rating:** -40.0 degrees celsius and 75.0 degrees celsius **Overall Width:** 6.437 inches **Minor Width:** Between 0.125 inches and 0.156 inches **Outside Corner Radius:** 0.125 inches **Aperture Width:** 5.438 inches **Aperture Length:** 13.500 inches Center To Center Distance Between Bolt Holes Along Width: 3.500 inches Center To Center Distance Between Bolt Holes Along Length: 3.300 inches **Outside Edge To Bolt Hole Center Distance Along Width:** 0.219 inches **Outside Edge To Bolt Hole Center Distance Along Length:** 0.219 inches **Cross-sectional Height:** Between 0.046 inches and 0.091 inches **Minor Height:** Between 0.062 inches and 0.078 inches **Bolt Hole Quantity:** 12 **Environmental Protection Material Location:** Around rf shielding gasket outer perimeter Material: Rubber chloroprene class cr environmental seal **Material Specification:** Mil-r-6130, type 2, grade a, condition medium military specification single material response environmental seal Style Designator: Non-circular

Shelf Life:

N/a

NSN 5999-00-236-0320

Electronic Shielding Gasket - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6130 spec.