

View Online at <https://aerobasegroup.com/nsn/5999-00-240-3269>

**Body Style:**

Rectangular, bracketed

**Hole Diameter:**

Between 0.095 inches and 0.110 inches

**Overall Length:**

9.030 inches

**Frequency Rating:**

Between 0.500 megahertz and 13.000 megahertz

**Body Length:**

8.030 inches

**Body Width:**

0.650 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

8.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

5.000 volts

**Material And Location:**

Metal

**Input Impedance Rating:**

75.000 ohms

**Frequency Bandwidth:**

50.0 kilohertz

**Body Depth:**

1.530 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

350.000 nanoseconds single section

**Segment Quantity Per Section:**

5 single section

**Segment Delay Time:**

350.000 nanoseconds single section 5th segment

**Pulse Rise Time Rating:**

20.0 nanoseconds

**Terminal Type And Quantity:**

7 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100