NSN 5999-00-240-3269

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-240-3269

Body Style:		
Rectangular, bracketed		
Hole Diameter:		
Between 0.095 inches and 0.110 inches		
Overall Length:		
9.030 inches		
Frequency Rating:		
Between 0.500 megahertz and 13.000 megahertz		
Body Length:		
8.030 inches		
Body Width:		
0.650 inches		
Individual Section Quantity:		
1		
Longest Horizontal Distance Between Mounting Centers:		
8.500 inches		
Longest Vertical Distance Between Mounting Centers:		
1.000 inches		
Operating Tempurature Range:		
-55.0 to 85.0 degrees celsius		
Mounting Facility Quantity:		
4		
Voltage Rating:		
5.000 volts		
Material And Location:		
Metal		
Input Impedance Rating:		
75.000 ohms		
Frequency Bandwidth:		
50.0 kilohertz		
Body Depth:		
1.530 inches		
Mounting Facility:		
Unthreaded hole		
Mounting Provision Arrangement Style:		
Four position rectangular		
Attenuation In Decibels:		
1.000		
Signal Delay Method:		
Inductance		
Delay Time Variation Method:		

Tapped

NSN 5999-00-240-3269

Delay Line - Page 2 of 2



Section	Delay	ı ime:
050 000		

350.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

350.000 nanoseconds single section 5th segment

Pulse Rise Time Rating:

20.0 nanoseconds

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100