NSN 5999-00-241-7757

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-241-7757

| Thread Class: |
|-----------------------------------|
| 2a |
| Thread Pitch Diameters: |
| +0.142/+0.145 inches |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| 0.750 inches |
| Overall Diameter: |
| 0.500 inches |
| Mounting Facility Quantity: |
| 1 |
| Voltage Rating In Volts: |
| 115.0 ac |
| Current Rating In Amps: |
| 40.0 |
| Mounting Method: |
| Threaded stud |
| Thready Qty Per Inch (tpi): |
| 36 |
| Thread Size: |
| 0.164 inches |
| Material: |
| Silver contact |
| Precious Material And Location: |
| Contact and body silver |
| Precious Material And Weight: |
| 0.100 silver grains, troy |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Any acceptable body |
| Style Designator: |
| Round flatted fixed point contact |
| Thread Series Designator: |
| Unf |
| Terminal Type And Quantity: |
| 1 pin axially at one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5999-00-241-7757

Electrical Contact - Page 2 of 2



Demilitarization:

No

Fiig:

A222a0