NSN 5999-00-248-6847

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-248-6847 **Thread Class:** 2b **Thread Pitch Diameters:** +0.1140/+0.1160 inches **Body Style:** Rectangular, w/shaft **Slot Depth:** 0.047 inches **Overall Depth:** 2.750 inches **Slot Width:** 0.040 inches **Shaft Diameter:** 0.112 inches **Shaft Length:** 1.000 inches **Adjustment Device Quantity: Adjustment Device Drive Type:** Shaft **Body Length:** 1.250 inches **Body Width:** 1.250 inches **Shaft Style:** Round, slotted **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.750 inches **Longest Vertical Distance Between Mounting Centers:** 0.750 inches **Operating Tempurature Range:** +0.0/+50.0 degrees celsius **Mounting Facility Quantity: Body Depth:** 1.750 inches **Mounting Facility:**

Threaded hole

Mounting Provision Arrangement Style:

2 position diagonal

NSN 5999-00-248-6847Delay Line - Page 2 of 2



Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Variable
Section Delay Time:
2.400 microseconds single section and 2.900 microseconds single section
Pulse Rise Time Rating:
0.9 microseconds
Distance From End Of Body To Center Of Shaft:
0.875 inches
Distance From Bottom Of Body To Center Of Shaft:
0.625 inches
Terminal Type And Quantity:
2 wire hook
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100