

View Online at <https://aerobasegroup.com/nsn/5999-00-248-7240>

**Thread Class:**

2b

**Body Style:**

Rectangular, w/shaft

**Overall Depth:**

2.062 inches

**Frequency Rating:**

Not rated

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

4.250 inches

**Body Width:**

4.250 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.750 inches

**Longest Vertical Distance Between Mounting Centers:**

3.750 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

100.000 volts

**Material And Location:**

Metal case

**Input Impedance Rating:**

Not rated

**Output Impedance Rating:**

390.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

1.500 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

2.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

15.000 microseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

750.0 nanoseconds

**Distance From End Of Body To Center Of Shaft:**

2.125 inches

**Distance From Bottom Of Body To Center Of Shaft:**

2.125 inches

**Terminal Type And Quantity:**

4 solder stud

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100