## NSN 5999-00-248-7240

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-248-7240 **Thread Class:** 2b **Body Style:** Rectangular, w/shaft **Overall Depth:** 2.062 inches Frequency Rating: Not rated **Adjustment Device Quantity: Adjustment Device Drive Type:** Slotted screw **Body Length:** 4.250 inches **Body Width:** 4.250 inches **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** 3.750 inches **Longest Vertical Distance Between Mounting Centers:** 3.750 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Mounting Facility Quantity:** 4 Voltage Rating: 100.000 volts **Material And Location:** Metal case Input Impedance Rating: **Output Impedance Rating:** 390.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 1.500 inches

**Mounting Facility:** Threaded hole

**Mounting Provision Arrangement Style:** 

Four position rectangular

## **NSN 5999-00-248-7240**Delay Line - Page 2 of 2



Attenuation In Decibels:
2.500
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Variable
Section Delay Time:
15.000 microseconds single section
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
750.0 nanoseconds
Distance From End Of Body To Center Of Shaft:
2.125 inches
Distance From Bottom Of Body To Center Of Shaft:
2.125 inches
Terminal Type And Quantity:
4 solder stud
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A32100