NSN 5999-00-249-7016

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-249-7016 **Body Style:** Rectangular, w/shaft **Overall Depth:** 4.120 inches **Shaft Length:** 0.340 inches Frequency Rating: Not rated **Adjustment Device Quantity: Adjustment Device Drive Type:** Shaft **Body Length:** 0.750 inches **Body Width:** 0.350 inches **Shaft Style:** Round, slotted **Individual Section Quantity: Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 4 Voltage Rating: 300.000 volts **Material And Location:** Copper terminal Input Impedance Rating: 200.000 ohms **Output Impedance Rating:** 200.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 4.000 inches **Mounting Facility: Terminal**

Attenuation In Decibels: 0.500

NSN 5999-00-249-7016Delay Line - Page 2 of 2



Signal Delay Method:	
Inductance	
Delay Time Variation Method:	
Adjustable	
Section Delay Time:	
100.000 nanoseconds single section	
Delay Time Variation Per Deg Celsius:	
1.000 nanoseconds	
Pulse Rise Time Rating:	
Not rated	
Distance From End Of Body To Center Of Shaft:	
0.500 inches	
Distance From Bottom Of Body To Center Of Shaft:	
0.170 inches	
Terminal Type And Quantity:	
4 wire leads	
Shelf Life:	
N/a	
Unit Of Measure:	
.	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A32100	