

View Online at <https://aerobasegroup.com/nsn/5999-00-299-1204>

Thread Class:

2a

Thread Pitch Diameters:

+0.0312 to 0.0313 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

3.040 inches

Body Width:

2.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Stud Length:

0.480 inches

Mounting Facility Quantity:

4

Voltage Rating:

50.000 volts

Material And Location:

Steel

Surface Treatment And Location:

Tin plated, mil-t-10727, type 2

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

1.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.000

Signal Delay Method:

Electromechanical

Delay Time Variation Method:

Tapped

Section Delay Time:

10.500 microseconds single section

Segment Quantity Per Section:

6 single section

Segment Delay Time:

9.500 microseconds single section 5th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

500.0 nanoseconds

Terminal Type And Quantity:

9 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar set, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100