NSN 5999-00-309-7892



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-309-7892 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 6.813 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 5.600 inches **Operating Tempurature Range:** +0.0 to 70.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** Not rated Input Impedance Rating: 180.000 ohms **Output Impedance Rating:** 180.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.350 inches **Mounting Facility:** Terminal, wire-lead **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 1.900 **Signal Delay Method:** Inductance **Delay Time Variation Method: Tapped Section Delay Time:** 420.000 nanoseconds single section **Segment Quantity Per Section:** 15 single section

Segment Delay Time:

28.000 nanoseconds single section 9th segment

NSN 5999-00-309-7892

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
50.0 nanoseconds
Terminal Type And Quantity:
23 wire leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100