

View Online at <https://aerobasegroup.com/nsn/5999-00-310-9927>

**Body Style:**

Rectangular, bracketed

**Hole Diameter:**

0.156 inches

**Overall Length:**

1.750 inches

**Frequency Rating:**

Not rated

**Body Length:**

1.000 inches

**Body Width:**

4.500 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

4.000 inches

**Longest Vertical Distance Between Mounting Centers:**

1.500 inches

**Operating Temperature Range:**

-40.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Steel case

**Surface Treatment And Location:**

Enamel, dull gray, metallic case

**Input Impedance Rating:**

1.350 kilohms

**Output Impedance Rating:**

1.350 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

4.500 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Section Delay Time:**

416.000 nanoseconds 2nd section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

5 tab solder lug

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100