NSN 5999-00-311-3318

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-311-3318 **Body Style:** Rectangular, bracketed **Overall Length:** 8.000 inches Frequency Rating: Not rated **Body Length:** 7.375 inches **Body Width:** 4.000 inches **Individual Section Quantity: Operating Tempurature Range:** -40.0 to 105.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 75.000 volts **Material And Location:** Any acceptable case **Surface Treatment And Location:** Enamel, mil-e-15090, type 3, class 2 case Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 180.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 2.000 inches **Mounting Facility: Terminal Attenuation In Decibels:** 8.000 **Signal Delay Method:** Inductance **Delay Time Variation Method:** Tapped **Section Delay Time:**

23.400 microseconds single sectionSegment Quantity Per Section:15 single section

NSN 5999-00-311-3318

Delay Line - Page 2 of 2



	Segment	Delay	Time:
--	---------	-------	-------

8.700 microseconds single section 7th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

0.1 microseconds

Terminal Type And Quantity:

4 wire leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100