

View Online at <https://aerobasegroup.com/nsn/5999-00-311-3319>

Body Style:

Cylindrical, bracketed

Hole Diameter:

0.180 inches

Overall Depth:

0.500 inches

Overall Width:

0.937 inches

Body Length:

4.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.500 inches

Operating Temperature Range:

+0.0/+105.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

100.000 pounds per hour wet

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, mil-e-15090, type 3, class 2 case

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

7200.0 kilohertz

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

3.000

Signal Delay Method:

Inductance

Section Delay Time:

400.000 nanoseconds single section

Pulse Rise Time Rating:

50.0 nanoseconds

Terminal Type And Quantity:

3 pin

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100