

View Online at <https://aerobasegroup.com/nsn/5999-00-311-3319>

**Body Style:**

Cylindrical, bracketed

**Hole Diameter:**

0.180 inches

**Overall Depth:**

0.500 inches

**Overall Width:**

0.937 inches

**Body Length:**

4.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.500 inches

**Operating Temperature Range:**

+0.0/+105.0 degrees celsius

**Mounting Facility Quantity:**

2

**Voltage Rating:**

100.000 pounds per hour wet

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 3, class 2 case

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

7200.0 kilohertz

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

3.000

**Signal Delay Method:**

Inductance

**Section Delay Time:**

400.000 nanoseconds single section

**Pulse Rise Time Rating:**

50.0 nanoseconds

**Terminal Type And Quantity:**

3 pin

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100