

View Online at <https://aerobasegroup.com/nsn/5999-00-323-0587>

Thread Class:

2a

Thread Pitch Diameters:

+0.1141/+0.1169 inches

Body Style:

Rectangular, front connection

Overall Depth:

2.560 inches

Body Length:

1.000 inches

Body Width:

1.000 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

0.590 inches

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Stud Length:

0.380 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Input Impedance Rating:

1.300 kilohms

Output Impedance Rating:

1.300 kilohms

Body Depth:

2.120 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

137.000 nanoseconds all sections

Segment Quantity Per Section:

2 all sections

Segment Delay Time:

68.500 nanoseconds all sections all segments

Pulse Rise Time Rating:

40.0 nanoseconds

Terminal Type And Quantity:

6 wire loop

Test Data Document:

82577-943602 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100