## NSN 5999-00-325-8709

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-325-8709

| Cross Sectional Shape:   |
|--|
| Emi  |
| Hole Diameter:   |
| 0.170 inches   |
| Overall Length:  |
| 8.000 inches   |
| Overall Width:   |
| 6.000 inches   |
| Outside Corner Radius:   |
| 0.125 inches   |
| Aperture Width:  |
| 5.000 inches   |
| Aperture Length:   |
| 7.000 inches   |
| Center To Center Distance Between Bolt Holes Along Width:  |
| 3.000 inches   |
| Center To Center Distance Between Bolt Holes Along Length:   |
| 3.000 inches   |
| Outside Edge To Bolt Hole Center Distance Along Width:   |
| 0.250 inches   |
| Outside Edge To Bolt Hole Center Distance Along Length:  |
| 0.250 inches   |
| Cross-sectional Height:  |
| 0.593 inches   |
| Bolt Hole Quantity:  |
| 10   |
| Environmental Protection Material Location:  |
| Throughout rf shielding gasket   |
| Material:  |
| Steel comp 1010 emi/rfi conductor  |
| Material Specification:  |
| Mil-r-6130, type 2, grade a, condition medium military specification single material response environmental seal |
| Surface Treatment:   |
| Cadmium emi/rfi conductor and copper emi/rfi conductor and tin emi/rfi conductor                                 |
| Surface Treatment Specification:   |
| Qq-p-416, type 1, class 2 federal specification 1st treatment response emi/rfi conductor                         |
| Style Designator:  |
| Non-circular   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5999-00-325-8709

Electronic Shielding Gasket - Page 2 of 2



Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6130 spec.