NSN 5999-00-325-8999



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-325-8999 **Body Style:** Rectangular, top connection **Overall Width:** Between 3.234 inches and 3.438 inches Frequency Rating: Not rated **Body Length:** 8.240 inches **Body Width:** 3.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 9.160 inches **Operating Tempurature Range:** -55.0 to 85.0 degrees celsius **Mounting Facility Quantity:** 2 **Voltage Rating:** 100.000 millivolts **Material And Location:** Aluminum alloy, qq-a-225/5, alloy 2017, t4 **Surface Treatment And Location:** Anodized, mil-a-8625, type 3, class 1 Input Impedance Rating: 25.000 ohms **Output Impedance Rating:** 95.000 ohms Frequency Bandwidth: 200.0 kilohertz **Body Depth:** 2.000 inches **Mounting Facility: Bracket Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:**

2.000 **Signal Delay Method:** Inductance **Section Delay Time:**

68.250 microseconds single section

NSN 5999-00-325-8999

Delay Line - Page 2 of 2



Delay Time	Variation	Per Deg	Celsius:
------------	-----------	---------	----------

Not rated

Pulse Rise Time Rating:

2.0 microseconds

Terminal Type And Quantity:

2 coaxial receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100