

View Online at <https://aerobasegroup.com/nsn/5999-00-332-2931>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.0997/+0.1177 inches

**Body Style:**

Rectangular

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.500 inches

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

4.875 inches

**Body Width:**

2.250 inches

**Shaft Style:**

Round

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.375 inches

**Longest Vertical Distance Between Mounting Centers:**

1.375 inches

**Operating Temperature Range:**

+0.0/+75.0 degrees celsius

**Stud Length:**

0.500 inches

**Mounting Facility Quantity:**

4

**Material And Location:**

Steel, qq-s-763, class 303, cond a

**Surface Treatment And Location:**

Enamel, tt-e-516

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Body Depth:**

2.125 inches

**Step Quantity:**

10

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

3.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Adjustable

**Delay Time Per Step:**

0.100 microseconds

**Section Delay Time:**

1.000 microseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

0.100 microseconds single section all segments

**Pulse Rise Time Rating:**

50.0 milliseconds

**Terminal Type And Quantity:**

3 wire hook

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100