

View Online at <https://aerobasegroup.com/nsn/5999-00-332-2931>

Thread Class:

2a

Thread Pitch Diameters:

+0.0997/+0.1177 inches

Body Style:

Rectangular

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

4.875 inches

Body Width:

2.250 inches

Shaft Style:

Round

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.375 inches

Longest Vertical Distance Between Mounting Centers:

1.375 inches

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Stud Length:

0.500 inches

Mounting Facility Quantity:

4

Material And Location:

Steel, qq-s-763, class 303, cond a

Surface Treatment And Location:

Enamel, tt-e-516

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

2.125 inches

Step Quantity:

10

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Adjustable

Delay Time Per Step:

0.100 microseconds

Section Delay Time:

1.000 microseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

0.100 microseconds single section all segments

Pulse Rise Time Rating:

50.0 milliseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100