NSN 5999-00-333-7943

Electrical Contact - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5999-00-333-7943



Identification Code Color: Red and white and white **Overall Length:** 1.505 inches **Overall Diameter:** Between 0.409 inches and 0.419 inches **Cable Entrance Diameter:** Between 0.279 inches and 0.286 inches **Pin Accommodation Length:** 0.625 inches **Pin Accommodation Diameter:** Between 0.228 inches and 0.232 inches **Retention Groove Diameter:** Between 0.307 inches and 0.310 inches **Mounting Method:** Force fit **Crimping Tool Identifying Number:** M22520/23-01 **Special Features:** Basic item identification number bin-299 Material: Copper alloy body **Precious Material And Location:** Body and contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold Surface Treatment: Gold body and contact Surface Treatment Specification: Mil-g-45204, type 1, class 2, grade c military specification single treatment response body and contact Style Designator: Socket contact **Test Data Document:** 81349-mil-c-23216 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 crimp end opposite contact

Specification Data:

81349-mil-c-39029/45 government specification

Shelf Life:

N/a

NSN 5999-00-333-7943

Electrical Contact - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-g-45204 spec.