

View Online at <https://aerobasegroup.com/nsn/5999-00-333-8615>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1399 to 0.1428 inches

**Body Style:**

Cylindrical

**Body Diameter:**

1.656 inches

**Frequency Rating:**

Not rated

**Body Length:**

3.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.844 inches

**Operating Temperature Range:**

Not rated

**Stud Length:**

0.344 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2

**Voltage Rating:**

Not rated

**Material And Location:**

Metal body

**Surface Treatment And Location:**

Any acceptable body

**Input Impedance Rating:**

3.200 kilohms

**Output Impedance Rating:**

3.200 kilohms

**Frequency Bandwidth:**

Not rated

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

16.000 microseconds single section

**Segment Quantity Per Section:**

3 single section

**Segment Delay Time:**

8.000 microseconds single section 3rd segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

2.05 microseconds

**Terminal Type And Quantity:**

5 tab solder lug

**Thread Size And Series/type Designator:**

0.164-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A32100