

View Online at <https://aerobasegroup.com/nsn/5999-00-333-8615>

Thread Class:

2a

Thread Pitch Diameters:

+0.1399 to 0.1428 inches

Body Style:

Cylindrical

Body Diameter:

1.656 inches

Frequency Rating:

Not rated

Body Length:

3.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.844 inches

Operating Temperature Range:

Not rated

Stud Length:

0.344 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Voltage Rating:

Not rated

Material And Location:

Metal body

Surface Treatment And Location:

Any acceptable body

Input Impedance Rating:

3.200 kilohms

Output Impedance Rating:

3.200 kilohms

Frequency Bandwidth:

Not rated

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

16.000 microseconds single section

Segment Quantity Per Section:

3 single section

Segment Delay Time:

8.000 microseconds single section 3rd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.05 microseconds

Terminal Type And Quantity:

5 tab solder lug

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100