NSN 5999-00-334-0063

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-334-0063 **Body Style:** Rectangular Slot Length: 0.375 inches **Shaft Diameter:** Any acceptable **Shaft Length:** 8.375 inches Frequency Rating: Not rated **Adjustment Device Quantity: Adjustment Device Drive Type:** Shaft **Body Length:** 9.500 inches **Body Width:** 2.375 inches **Shaft Style:** Round **Individual Section Quantity:** 2 **Longest Horizontal Distance Between Mounting Centers:** 9.062 inches **Operating Tempurature Range:** -50.0 to 60.0 degrees celsius **Mounting Facility Quantity:** Voltage Rating: 600.000 volts **Material And Location:** Aluminum case **Surface Treatment And Location:** Paint Input Impedance Rating: 470.000 ohms **Output Impedance Rating:** 470.000 ohms Frequency Bandwidth: Not rated

Body Depth: 1.062 inches

NSN 5999-00-334-0063Delay Line - Page 2 of 2



Mounting Facility:
Slotted hole
Mounting Provision Arrangement Style:
2 position in-line
Attenuation In Decibels:
Not rated
Signal Delay Method:
Inductance
Delay Time Variation Method:
Variable
Section Delay Time:
1.900 microseconds 2nd section
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
1 turret
Slotted Hole Width:
0.156 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A32100