

View Online at <https://aerobasegroup.com/nsn/5999-00-348-0353>

Thread Class:

2a

Thread Pitch Diameters:

Any acceptable

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

4.281 inches

Body Width:

2.312 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

3.718 inches

Longest Vertical Distance Between Mounting Centers:

2.500 inches

Operating Temperature Range:

Not rated

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Steel, mil-s-4043, type 304 body

Surface Treatment And Location:

Tin plated, mil-t-10727, type 1 body

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

3.438 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

400.000 nanoseconds 2nd section

Segment Quantity Per Section:

17 4th section

Segment Delay Time:

700.000 nanoseconds 4th section 2nd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

24 turret

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100