

View Online at <https://aerobasegroup.com/nsn/5999-00-348-0353>

**Thread Class:**

2a

**Thread Pitch Diameters:**

Any acceptable

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

4.281 inches

**Body Width:**

2.312 inches

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

3.718 inches

**Longest Vertical Distance Between Mounting Centers:**

2.500 inches

**Operating Temperature Range:**

Not rated

**Stud Length:**

0.375 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Steel, mil-s-4043, type 304 body

**Surface Treatment And Location:**

Tin plated, mil-t-10727, type 1 body

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

3.438 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

400.000 nanoseconds 2nd section

**Segment Quantity Per Section:**

17 4th section

**Segment Delay Time:**

700.000 nanoseconds 4th section 2nd segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

24 turret

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100