NSN 5999-00-400-3286

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-400-3286 **Body Style:** Rectangular **Slot Depth:** Between 0.025 inches and 0.035 inches **Slot Width:** Between 0.020 inches and 0.024 inches **Shaft Diameter:** 0.080 inches **Shaft Length:** 0.430 inches Frequency Rating: Not rated **Adjustment Device Quantity: Adjustment Device Drive Type: Body Length:** 2.810 inches **Body Width:** 1.000 inches **Shaft Style:** Round, slotted **Individual Section Quantity: Operating Tempurature Range:** -30.0 to 70.0 degrees celsius Voltage Rating: Not rated **Material And Location:** Plastic case Input Impedance Rating: Not rated **Output Impedance Rating:** 1150.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.610 inches **Mounting Facility:** Pin

Attenuation In Decibels:

Not rated

NSN 5999-00-400-3286Delay Line - Page 2 of 2



Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Variable
Section Delay Time:
5.000 nanoseconds single section
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
100.0 nanoseconds
Terminal Type And Quantity:
4 pin
Fsc Application Data:
Multiplier, amplifer, computer-recorder group, sonar
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100