NSN 5999-00-400-3286

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-400-3286

Body Style:
Rectangular
Slot Depth:
Between 0.025 inches and 0.035 inches
Slot Width:
Between 0.020 inches and 0.024 inches
Shaft Diameter:
0.080 inches
Shaft Length:
0.430 inches
Frequency Rating:
Not rated
Adjustment Device Quantity:
1
Adjustment Device Drive Type:
Shaft
Body Length:
2.810 inches
Body Width:
1.000 inches
Shaft Style:
Round, slotted
Individual Section Quantity:
1
Operating Tempurature Range:
-30.0 to 70.0 degrees celsius
Voltage Rating:
Not rated
Material And Location:
Plastic case
Input Impedance Rating:
Not rated
Output Impedance Rating:
1150.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
0.610 inches
Mounting Facility:
Pin
Attenuation In Decibels:
Not rated

NSN 5999-00-400-3286

Delay Line - Page 2 of 2



Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Variable
Section Delay Time:
5.000 nanoseconds single section
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
100.0 nanoseconds
Terminal Type And Quantity:
4 pin
Fsc Application Data:
Multiplier, amplifer, computer-recorder group, sonar
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100