

View Online at <https://aerobasegroup.com/nsn/5999-00-402-2882>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.0813 to 0.1120 inches

**Body Style:**

Rectangular, front connection

**Overall Depth:**

0.875 inches

**Frequency Rating:**

10.500 megahertz

**Body Length:**

2.000 inches

**Body Width:**

1.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.625 inches

**Operating Temperature Range:**

+0.0 to 65.0 degrees celsius

**Mounting Facility Quantity:**

2

**Voltage Rating:**

36.000 volts

**Input Impedance Rating:**

78.000 ohms

**Output Impedance Rating:**

78.000 ohms

**Frequency Bandwidth:**

2.250 kilohertz

**Body Depth:**

0.750 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

20.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

3.050 nanoseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

2 wire hook

**Thread Size And Series/type Designator:**

0.112-40 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100