

View Online at <https://aerobasegroup.com/nsn/5999-00-402-2882>

Thread Class:

2a

Thread Pitch Diameters:

+0.0813 to 0.1120 inches

Body Style:

Rectangular, front connection

Overall Depth:

0.875 inches

Frequency Rating:

10.500 megahertz

Body Length:

2.000 inches

Body Width:

1.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.625 inches

Operating Temperature Range:

+0.0 to 65.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

36.000 volts

Input Impedance Rating:

78.000 ohms

Output Impedance Rating:

78.000 ohms

Frequency Bandwidth:

2.250 kilohertz

Body Depth:

0.750 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

20.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

3.050 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

2 wire hook

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100