NSN 5999-00-406-1840



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-406-1840 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 6.417 inches **Body Width:** 3.690 inches **Individual Section Quantity: Operating Tempurature Range:** +0.0 to 75.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** Not rated **Material And Location:** Steel case **Surface Treatment And Location:** Enamel, mil-e-15090, type 1, class 2 case Input Impedance Rating: 45.000 kilohms **Output Impedance Rating:** 45.000 kilohms Frequency Bandwidth: Not rated **Body Depth:** 0.719 inches **Mounting Facility:** Connector **Attenuation In Decibels:** Not rated **Signal Delay Method:** Inductance **Delay Time Variation Method: Tapped Section Delay Time:** 94.400 microseconds single section **Segment Quantity Per Section:**

4 single section

Segment Delay Tin

Segment Delay Time:

30.400 microseconds single section 3rd segment

NSN 5999-00-406-1840

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
1 connector, receptacle
Fsc Application Data:

Except testing, multiapplication

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100