NSN 5999-00-411-9495

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-411-9495 **Thread Class:** 2a **Thread Pitch Diameters:** +0.0813/+0.1120 inches **Body Style:** Rectangular Frequency Rating: Between 8.250 megahertz and 12.750 megahertz **Body Length:** 2.000 inches **Body Width:** 1.500 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.625 inches **Operating Tempurature Range:** +0.0/+65.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 2 **Voltage Rating:** 100.000 volts Input Impedance Rating: 78.000 ohms **Output Impedance Rating:** 78.000 ohms **Body Depth:** 0.750 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 20.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:**

Tapped

Section Delay Time:

12.905 microseconds single section

NSN 5999-00-411-9495

Delay Line - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

2 wire hook

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100