

View Online at <https://aerobasegroup.com/nsn/5999-00-411-9498>

Thread Class:

2a

Thread Pitch Diameters:

+0.0813/+0.1120 inches

Body Style:

Capsule, divided

Frequency Rating:

Between 8.250 megahertz and 12.750 megahertz

Body Length:

2.000 inches

Body Width:

1.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.625 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Voltage Rating:

100.000 volts

Input Impedance Rating:

78.000 ohms

Output Impedance Rating:

78.000 ohms

Frequency Bandwidth:

10500.0 kilohertz

Body Depth:

0.750 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

20.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

22.815 microseconds single section and 22.905 microseconds single section

Pulse Rise Time Rating:

1.5 microseconds

Terminal Type And Quantity:

3 tab solder lug

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100