## NSN 5999-00-420-1443

Electrical Contact - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5999-00-420-1445
dentification Code Color:
Orange and black and gray
Overall Length:
0.718 inches
Overall Diameter:
Between 0.130 inches and 0.133 inches
Cable Entrance Diameter:
0.068 inches
Pin Accommodation Length:
Between 0.270 inches and 0.320 inches
Pin Accommodation Diameter:
0.064 inches
Retention Groove Diameter:
0.099 inches
Mounting Method:
Force fit
Material:
Copper alloy body
Precious Material And Location:
External surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Surface Treatment:
Gold contact and copper contact
Surface Treatment Specification:
Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response body and contact
Style Designator:
Socket contact
Test Data Document:
31349-mil-c-39029 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 crimp and solder end opposite contact
Specification Data:
31349-mil-c-39029/46 government specification
Shelf Life:
N/a
Unit Of Measure:
-

No

Demilitarization:

## NSN 5999-00-420-1443

Electrical Contact - Page 2 of 2



Fiig:

A222a0

Mil-std (military Standard):

Mil-g-45204 spec.