

View Online at <https://aerobasegroup.com/nsn/5999-00-421-7386>

Frequency Rating:

1.000 megahertz

Longest Horizontal Distance Between Mounting Centers:

6.000 inches

Longest Vertical Distance Between Mounting Centers:

6.000 inches

Operating Temperature Range:

-40.0 to 55.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

6.500 kilohms

Frequency Bandwidth:

3600.0 kilohertz

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Transmission line

Delay Time Variation Method:

Variable

Section Delay Time:

3.333 milliseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

9 tab solder lug

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Interrogator sets, electronic identification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100