

View Online at <https://aerobasegroup.com/nsn/5999-00-421-7386>

**Frequency Rating:**

1.000 megahertz

**Longest Horizontal Distance Between Mounting Centers:**

6.000 inches

**Longest Vertical Distance Between Mounting Centers:**

6.000 inches

**Operating Temperature Range:**

-40.0 to 55.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

6.500 kilohms

**Frequency Bandwidth:**

3600.0 kilohertz

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Transmission line

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

3.333 milliseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

9 tab solder lug

**Thread Size And Series/type Designator:**

0.164-32 unc

**Fsc Application Data:**

Interrogator sets, electronic identification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100