

View Online at <https://aerobasegroup.com/nsn/5999-00-450-4848>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.0958 to 0.0991 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

3.000 inches

**Body Width:**

2.000 inches

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

2.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.500 inches

**Operating Temperature Range:**

-54.0 to 85.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

500.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.500 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

2.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

14.500 microseconds 1st section

**Segment Quantity Per Section:**

6 1st section

**Segment Delay Time:**

8.500 microseconds 1st section 1st segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

2.0 microseconds

**Terminal Type And Quantity:**

14 tab solder lug

**Thread Size And Series/type Designator:**

0.112-40 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100