NSN 5999-00-450-4848



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-450-4848 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0958 to 0.0991 inches **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 3.000 inches **Body Width:** 2.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.500 inches **Longest Vertical Distance Between Mounting Centers:** 1.500 inches **Operating Tempurature Range:** -54.0 to 85.0 degrees celsius **Inclosure Type:** Encased **Mounting Facility Quantity: Voltage Rating:** Not rated Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.500 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular

Signal Delay Method:

2.000

Inductance

Attenuation In Decibels:

NSN 5999-00-450-4848Delay Line - Page 2 of 2



Delay Time Variation Method:
Tapped
Section Delay Time:
14.500 microseconds 1st section
Segment Quantity Per Section:
6 1st section
Segment Delay Time:
8.500 microseconds 1st section 1st segment
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
2.0 microseconds
Terminal Type And Quantity:
14 tab solder lug
Thread Size And Series/type Designator:
0.112-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100